

Leona™ 1300G

Asahi Kasei Corporation - Polyamide 66

Tuesday, October 10, 2017

General Information						
General						
Material Status	Commercial: Active					
Availability	Africa & Middle East	• Europe				
	 Asia Pacific 	North America				
Filler / Reinforcement	 Glass Fiber 					
Features	Creep Resistant	High Stiffness				
	 Fatigue Resistant 	High Strength				
Uses	 Automotive Applications 	Electrical/Electronic Applications				
	 Automotive Under the Hood 	Structural Parts				
Automotive Specifications	• GM GMP.PA66.065					

ASTM & ISO Properties ¹							
Physical	Dry	Conditioned	Unit	Test Method			
Density / Specific Gravity	1.39		g/cm³	ASTM D792 ISO 1183			
Molding Shrinkage				Internal Method			
Across Flow	0.90		%				
Flow	0.40		%				
Water Absorption							
Saturation, 23°C		1.7	%				
Equilibrium, 23°C, 50% RH		1.7	%	ISO 62			
Mechanical	Dry	Conditioned	Unit	Test Method			
Tensile Modulus (23°C)	10000	8000	MPa	ISO 527-2			
Tensile Stress							
Break, 23°C	190	135	MPa	ISO 527-2			
	186	132	MPa	ASTM D638			
Tensile Elongation							
Break	3.0	5.0	%	ASTM D638			
Break, 23°C	3.0	5.0	%	ISO 527-2			
Flexural Modulus							
	9300	6300	MPa	ASTM D790			
23°C	9000	6800	MPa	ISO 178			
Flexural Strength							
	289	216	MPa	ASTM D790			
23°C	275	202	MPa	ISO 178			
Taber Abrasion Resistance				ASTM D1044			
1000 Cycles		15.0	mg				
Impact	Dry	Conditioned	Unit	Test Method			
Charpy Notched Impact Strength	11	16	kJ/m²	ISO 179			
Charpy Unnotched Impact Strength	72	83	kJ/m²	ISO 179			
Notched Izod Impact	130	150	J/m	ASTM D256			

Disclaimer:

- Data shown are typical values obtained by proper testing methods and shoud not be used for specification purpose. Please use these data for selecting the most appropriate grade suitable for specific usage.

- These data may be changed because of improvement in properties.

 Be sure to read the relevant SDS before handling and use, and always follow the Important Precautions.

 Do not use plastics in any of the following orally-or medically-related applications.
- Orally-related application: any part, device or component which may come into direct oral contact or into direct contact with drinking foods or beverages. For drinking water application, please consult Asahi Ksei Chemicals Corporation.
- Medically-related applications: any part,or component which may be used intracorporeally or which may in dialysis or other processes come into direct or indirect contact with body tissue, body fluids, or transfusion fluids.

Leona™ 1300G

Asahi Kasei Corporation - Polyamide 66

Hardness	Dry	Conditioned	Unit	Test Method
Rockwell Hardness				ASTM D785
M-Scale	96	75		ISO 2039-2
R-Scale	120	112		
Thermal	Dry	Conditioned	Unit	Test Method
Deflection Temperature Under Load				
0.45 MPa, Unannealed	260		°C	ASTM D648
0.45 MPa, Unannealed	265		°C	ISO 75-2/B
1.8 MPa, Unannealed	250		°C	ASTM D648 ISO 75-2/A
CLTE - Flow	3.0E-5		cm/cm/°C	ASTM D696
Specific Heat	1590		J/kg/°C	
Thermal Conductivity	0.30		W/m/K	
Electrical	Dry	Conditioned	Unit	Test Method
Surface Resistivity	1.0E+15		ohms	ASTM D257 IEC 60093
Volume Resistivity				
	1.0E+15		ohms∙cm	ASTM D257
23°C	1.0E+15		ohms∙cm	IEC 60093
Dielectric Strength	28		kV/mm	ASTM D149 IEC 60243-1
Comparative Tracking Index				IEC 60112
3.00 mm	600		V	
Flammability	Dry	Conditioned	Unit	Test Method
Flame Rating (0.75 mm)	НВ			UL 94

Notes

Disclaimer:

¹ Typical properties: these are not to be construed as specifications.

Data shown are typical values obtained by proper testing methods and shoud not be used for specification purpose. Please use these data for selecting the most appropriate grade suitable for specific usage.

These data may be changed because of improvement in properties.

- Be sure to read the relevant SDS before handling and use, and always follow the Important Precautions.

- Do not use plastics in any of the following orally-or medically-related applications.

⁻ Orally-related application: any part, device or component which may come into direct oral contact or into direct contact with drinking foods or beverages.

For drinking water application, please consult Asahi Ksei Chemicals Corporation.

- Medically-related applications: any part, or component which may be used intracorporeally or which may in dialysis or other processes come into direct or indirect contact with body tissue, body fluids, or transfusion fluids.